

# Matrox Rapixo CXP >>>

Single- to quad-input CoaXPress® 2.0 frame grabbers with optional FPGA-based image processing offload



## Matrox Rapixo CXP at a glance

**CXP-12** Support for the highest speeds available in CXP 2.0



Connect to and capture from up to four cameras or combine connections for even higher data rates



PoCXP support simplifies cabling between cameras and vision computer



Offload host computer of custom image processing using a FPGA device



Auxiliary I/Os per CXP connection to synchronize with sensors, encoders, and controllers



License fingerprint for MIL software avoids the need for a separate hardware key

## Interface cards for high-speed imaging

Matrox® Rapixo CXP is a new generation of frame grabbers, supporting version 2.0 of the CoaXPress® (CXP) digital interface standard for machine vision applications. The Matrox Rapixo CXP family supports data rates of either up to 6.25 Gbps (CXP-6) or up to 12.5 Gbps (CXP-12) per connection. The PCIe® host interface comfortably matches the maximum input bandwidth from the CXP links. The CXP links are accessed through high-density BNC connectors allowing for a homogenous interconnection with new cameras. Power-over-CoaXPress (PoCXP) support on each connection simplifies system configurations, combining the camera's power interface with its command- and data-interface onto the same coaxial cable.

The Matrox Rapixo CXP family of frame grabbers feature one, two, or four connections for interfacing to independent cameras. Matrox Rapixo CXP Dual and Quad can also handle higher data rates through connection aggregation. The Matrox Rapixo CXP family possess sufficient onboard memory to buffer incoming image data in situations where the host computer is temporarily unable to accept data. The fanless design for select models ensures extended use without maintenance.

## Offload host computer of custom image processing using a FPGA

The Matrox Rapixo CXP Pro makes use of a field-programmable gate array (FPGA) device from the Xilinx Kintex® UltraScale™ family for not only integrating the controlling, formatting, and streaming logic of the various interfaces, but also allowing developers to incorporate Matrox Imaging- or user-developed custom image pre-processing operations to offload from the host computer. A variety of FPGA sizes are available for the Matrox Rapixo CXP Pro, providing a range of solutions tailored to a given application. Operations performed on-board are controlled through Matrox Imaging Library (MIL) application-development software. Within MIL, an existing FPGA configuration can be rearranged to perform a required sequence of operations without necessarily having to generate a new FPGA configuration. Using the Matrox FPGA Development Kit (FDK), developers generate their own FPGA configurations with custom operations written in C/C++.


## Pairs with MIL<sup>1</sup> software

Matrox Rapixo CXP boards supports 64-bit Windows® and Linux® through the latest MIL software. The card also acts as a license fingerprint and can store a supplemental license for MIL software, avoiding the need for a separate hardware key.


## Field-proven development software

The Matrox Rapixo CXP family is supported by MIL<sup>1</sup> software—a comprehensive software development kit (SDK) with a 25-year history of reliable performance. This toolkit features interactive software and programming functions for image capture, processing, analysis, annotation, display, and archiving operations, with the accuracy and robustness needed to tackle the most demanding applications. Refer to the MIL datasheet for more information.

## Matrox Rapixo CXP Quad



## Matrox Rapixo CXP Single/Dual



## Specifications

Hardware		
Model	Matrox Rapixo CXP Quad	Matrox Rapixo CXP Single/Dual
Host interface		
Interconnect	PCIe 2.1 / 3.1 x8 <sup>2</sup>	PCIe 2.1 / 3.1 x4 <sup>2</sup>
Camera/video interface		
Standard	CXP version 2.0	
Configuration	Four (4) connections	One (1) or two (2) connection(s) <sup>3</sup>
Speeds (Per connection)	1.25 / 2.5 / 3.125 / 5 / 6.25 / 10 / 12.5 Gbps (CXP-1, 2, 3, 5, 6, 10, and 12 respectively)	
Streams	Up to eight (8) total	
Connectors	High-density BNC	
Power output	PoCXP	
Miscellaneous	Connection-status indicator LEDs	
Memory		
Type	DDR4 SDRAM	DDR3 SDRAM
Quantity	4 or 8 GB	1 or 2 GB
Purpose	Image buffering and processing	
Image processing capabilities		
On-board look-up tables	8- / 10- / 12-bit support	
On-board Bayer interpolation	GB, BG, GR, and RG pattern support	
On-board color space conversion	Input formats: 8-/16-bit mono/Bayer, 24-/48-bit packed BGR Output formats: 8-/16-bit mono, 24-/48-bit packed/planar BGR, 16-bit YUV, 16-bit YCbCr, 32-bit BGRa	
Custom processing	Matrox Imaging- or user-developed using Xilinx Vivado® Design Suite and Matrox FPGA Development Kit (FDK)	N/A
General purpose I/Os		
Types	Three (3) TTL I/Os per connector Two (2) LVDS inputs per connector One (1) LVDS output per connector Two (2) opto-isolated inputs per connector	
Connectors	Two (2) mDP connectors on main I/O bracket accessed through a mDP-to-HD15 adaptor	One (1) HD15 connector on main I/O bracket
	Two (2) HD15 connectors on secondary I/O bracket	
Physical		
Form factor	Half-length, full-height, PCIe add-in card	
Product dimensions (L x W x H)	16.76 x 1.871 x 11.12 cm (6.6 x 0.737 x 4.376 in) <sup>3</sup>	
Power consumption	17.33 W (typical) <sup>4</sup>	TBD
Environmental		
Operating temperature	0°C to 55°C (32°F to 131°F) <sup>5</sup>	
Operating relative humidity	Up to 95% (non-condensing)	
Certifications		
	FCC Class A CE Class A (EN55032, EN55024) ICES-003 / NMB-003 Class A RCM Class A KC Class A	
Software		
Compatible software	Matrox Imaging Library (MIL) 10 <sup>6</sup>	
Operating system support	Windows 7 (64-bit) Windows 10 (64-bit) Linux (64-bit)	
Licensing provisions	MIL license fingerprint and storage	

## Ordering Information

Hardware	
Part number	Description
<b>RAP 1G 1C12</b>	Matrox Rapixo CXP Single CXP-12 PCIe 2.1 x4 frame grabber with 1 GB DDR3 SDRAM and passive heatsink. Note: Cable adaptors for second and third GPIO sets sold separately.
<b>RAP 2G 2C12</b>	Matrox Rapixo CXP Dual CXP-12 PCIe 3.1 x4 frame grabber with 2 GB DDR3 SDRAM and passive heatsink. Note: Cable adaptors for second and third GPIO sets sold separately.
<b>RAP 4G 4C6</b>	Matrox Rapixo CXP Quad CXP-6 PCIe 2.1 x8 frame grabber with 4 GB DDR4 SDRAM and passive heatsink. Includes one (1) mDP-to-HD15 GPIO cable adaptor. Note: Cable adaptors for second, third, and fourth GPIO sets sold separately.
<b>RAP 4G 4C12</b>	Matrox Rapixo CXP Quad CXP-12 PCIe 3.1 x8 frame grabber with 4 GB DDR4 SDRAM and passive heatsink. Includes one (1) mDP-to-HD15 GPIO cable adaptor. Note: Cable adaptors for second, third, and fourth GPIO sets sold separately.
<b>RAP 8G 4C12 P352</b>	Matrox Rapixo CXP Pro Quad CXP-12 PCIe 3.1 x8 frame grabber with 8 GB DDR4 SDRAM, Xilinx Kintex Ultrascale KU035 FPGA, and active heatsink (fansink). Includes one (1) mDP-to-HD15 GPIO cable adaptor. Note: Cable adaptors for second, third, and fourth GPIO sets sold separately.
<u>Contact Matrox Imaging</u> for other part numbers.	

Accessories	
Part number	Description
<b>RAPACCKIT01</b>	Accessory kit for Matrox Rapixo CXP Quad. One (1) additional mDP-to-HD15 GPIO cable adaptor and one (1) secondary dual HD15 I/O bracket with ribbon cable.
<b>RAPACCKIT02</b>	Accessory kit for Matrox Rapixo CXP Single/Dual. Include one (1) secondary dual HD15 I/O bracket with ribbon cable.
<b>HDBNC2BNC</b>	One (1) 12 in or 30 cm HDBNC-male-to-BNC-female adaptor cable.

Software
Refer to <a href="#">MIL datasheet</a> and <a href="#">Matrox FDK datasheet</a> .

### Endnotes:

1. The software may be protected by one or more patents; see [www.matrox.com/patents](http://www.matrox.com/patents) for more information.
2. Model dependent.
3. Dimensions (length x width x height) are taken from bottom edge of goldfinger to top edge of board. These measurements do not include mounting bracket.
4. Matrox Rapixo CXP Pro model power consumption is dependent on FPGA device and onboard processing workload.
5. Models with passive heatsink require a minimum ventilation of 150 LFM (linear feet per minute) in a single board configuration. Contact a sales representative for ventilation requirement for multiple board configurations.
6. Through an update.

## The Matrox Imaging Advantage



### Assured Quality & Longevity

We adhere to industry best practices in all hardware manufacturing and software development; product designs pay careful attention to component selection to secure consistent long-term availability. Matrox Imaging is able to meet Copy Exact and Revision Change Control procurement requirements in particular circumstances, backed by our dedicated team of QA specialists.



### Trusted Industry Standards

Matrox Imaging champions industry standards in our design and production. We leverage these standards to deliver quality compatible products, protecting our customers' best interests by ensuring our hardware and software components work with as many third-party products as possible.



### Comprehensive Customer Support

Our devoted front-line support and applications teams are on call to offer timely product installation, usage, and integration assistance. Matrox Professional Services delivers deep technical assistance to help customers develop their particular applications in a timely fashion. Services include personalized training and device interfacing as well as application feasibility, prototyping, troubleshooting, and debugging.



### Tailored Customer Training

Matrox Vision Academy comprises online and on-premises training for our vision software tools. On-premises intensive training courses are regularly held at Matrox headquarters, and can also be customized for onsite delivery. Vision Academy online training platform hosts a comprehensive set of on-demand videos available when and where needed.



### Long-Standing Global Network

Matrox Imaging customers benefit from a global network of distributors who offer complementary products and support, and integrators who build customized vision systems. These relationships are built on years of mutual trust and span the globe, ensuring customer access to only the best assistance in the industry.



### **About Matrox Imaging**

Founded in 1976, Matrox is a privately held company based in Montreal, Canada. Imaging, Graphics, and Video divisions provide leading component-level solutions, leveraging the others' expertise and industry relations to provide innovative, timely products.

Matrox Imaging is an established and trusted supplier to top OEMs and integrators involved in machine vision, image analysis, and medical imaging industries. The components consist of smart cameras, vision controllers, I/O cards, and frame grabbers, all designed to provide optimum price-performance within a common software environment.

### **Contact Matrox**

[imaging.info@matrox.com](mailto:imaging.info@matrox.com)

**North America Corporate Headquarters:** 1 800-804-6243 or 514-822-6020

Serving: Canada, United States, Latin America, Europe, Asia, Asia-Pacific, and Oceania

[www.matrox.com/imaging](http://www.matrox.com/imaging)

The use of the terms "industrial" or "factory-floor" do not indicate compliance to any specific industrial standards.

© 2019 Matrox Electronic Systems, Ltd. All rights reserved. Matrox reserves the right to change specifications without notice. Matrox and Matrox product names are either trademarks and/or registered trademarks in Canada or other countries and/or trademarks of Matrox Electronic Systems, Ltd and/or Matrox Graphics Inc. All other company and product names are registered trademarks and/or trademarks of their respective owners. The information furnished herein is believed to be accurate and reliable at time of printing; however, no responsibility license is granted under any patents or patent rights of Matrox Electronic Systems, Ltd. 08/2019

**matrox®**